



### Specifications HC-PROX3 Reader (Dual Mount Mullion and Single Gang)

**Size (Mullion):** 4.5 x 1.6 x 0.75 inches (114 x 38 x 19 mm)  
**Size (Single Gang):** 5.8 x 2.9 x 0.8 inches (147 x 74 x 20 mm)  
**Weight:** 3 oz. (85 g)  
**Input Voltage b:** +5 to 14 VDC  
**Current Draw c:** 5 mA minimum, 45 mA typical, 80 mA peak  
**LED Indicator:** Four-State Standard (Red, Green, Amber, and Off)  
**Audio Tone:** Standard  
**Frequency:** 125 KHz excitation  
**Compatibility:** FarPointe, AWID, HID  
**Operating Temperature:** -40° C to +65° C  
**Colors:** Black  
**Metal Mounting:** May be mounted directly to metal.  
**Certifications:** CSA, UL, FCC, CE, C-Tick.

The multi-piece HC-PROX3 delivers non-contact read ranges up to 6 inches (152 mm), and operates from 5 to 14 VDC. Physical size is a compact 4.5 x 1.6 x 0.75 inches (114 x 38 x 19 mm) for mullion mounting and 5.8 x 2.9 x 0.8 inches (147 x 74 x 20 mm) for single gang mounting.

Mounting is simplified with horizontal and vertical mounting slots, instead of simple holes, which allow the reader to be conveniently adjusted and leveled. To allow both indoor and outdoor operation the electronics are secured in tamper-resistant epoxy potting.