



Specifications HC-P640

Read Range a: PSC-1 - Up to 6 inches (152 mm) PSM-2 - Up to 4 inches (102 mm)
PSI-4 - Up to 4 inches (102 mm) PSK-3 - Up to 3 inches (76 mm)
Size: 4.6 x 3 x 0.7 inches (117 x 77 x 18 mm)
Weight: 4 oz. (113 g)
Input Voltage b: +5 to 14 VDC
Current Draw c: 30 mA minimum, 50 mA typical, 115 mA peak
LED Indicator d: Four-State Standard (Red, Green, Amber, and Off)
Audio Tone: Standard
Frequency: 125 KHz excitation
Operating Temperature: -40° C to +65° C
Colors: Black and Off-White
Metal Mounting: May be mounted directly to metal.
Certifications: FCC, CE, C-Tick.

The single-piece HC- P640 delivers non-contact read ranges up to 6 inches (152 mm), and operates from 5 to 14 VDC. Physical size is a compact 4.6 x 3 x 0.70 inches (117 x 77 x 18 mm). Mounting is simplified with horizontal and vertical mounting slots, instead of holes, which allow the reader to be conveniently adjusted and leveled. To allow both indoor and outdoor operation the electronics are sealed in tamper resistant epoxy potting.



Specifications HC-P710

Read Range a: PSC-1 - Up to 15 inches (381 mm)
PSI-4 - Up to 10 inches (254 mm) PSK-3 - Up to 6 inches (152 mm)
Size: 8.5 x 6 x 1 inches (216 x 152 x 26 mm)
Weight: 22.4 oz. (635 g)
Input Voltage b: +5 to 16 VDC
Current Draw: 200 mA typical, 600mA peak
LED Indicator: Oversized Four-State Standard (Red, Green, Amber, and Off)
Audio Tone: Standard
Frequency: 125 KHz excitation
Operating Temperature: -40° C to +65° C
Colors: Black
Metal Mounting: US- size single gang wall box or non-metallic flat surfaces.
Certifications: CSA, UL, FCC, CE, C-Tick.

The single-piece, easy-to-install HC-P710 delivers non-contact read ranges up to 15 inches (381 mm), and operates from 5 to 16 VDC. Physical size is 8.5 x 6.0 x 1.0 inches (216x152x26 mm). Allowing for both indoor and outdoor operation, the electronics are secured in tamper-resistant epoxy potting.