




| | |
|---|--|
|  | <h3>Specifications HC-HARPS1</h3> <p>Read Range a: HC-P300 - Up to 4 inches (102 mm) P-600 - Up to 4 inches (102 mm) HC-P400 - Up to 1 inch (25 mm) P-700 - Up to 14 inches (356 mm) HC-P500 - Up to 5 inches (127 mm)</p> <p>Size: Nominal 3.4 x 2.2 x 0.06 inches (86 x 55 x 1.5 mm)</p> <p>Weight: 0.3 oz. (9 g)</p> <p>Operation: Passive (no battery)</p> <p>Frequency: 125 KHz excitation</p> <p>Humidity: 0-95% non-condensing</p> <p>Operating Temperature: -40° C to +65° C</p> <p>Material: ABS</p> <p>Color: Off-white</p> <p>Slot Punch: Vertical</p> <p>Marking: Date Code and ID</p> <p>The PSC-1 is based upon proven passive digital radio frequency identification (RFID) technology. Physical size is a nominal 3.4 x 2.2 x 0.06 inches (86x55x1.5 mm). It includes beveled edges, is constructed of durable ABS plastic and is backed by a lifetime warranty. A vertical slot punch is standard. Color is off-white.</p> |
|  | <h3>Specifications HC-HARPSK3</h3> <p>Read Range a: HC-P300 - Up to 2 inches (51 mm) P-600 - Up to 1 inches (25 mm) HC-P400 - Up to 1 inch (25 mm) HC-P700 - Up to 6 inches (152 mm) P-500 - Up to 3 inches (76 mm)</p> <p>Size: Nominal 1.5 x 1.2 x 0.15 inches (36 x 29 x 3.8 mm)</p> <p>Weight: 0.16 oz. (4.5 g)</p> <p>Operation: Passive (no battery)</p> <p>Frequency: 125 KHz excitation</p> <p>Humidity: 0-95% non-condensing</p> <p>Operating Temperature: -40° C to +65° C</p> <p>Material: ABS</p> <p>Color: Light Gray</p> <p>Eyelet: Reinforced Brass</p> <p>Marking: Date Code and ID</p> <p>The PSK-3 is manufactured of light gray ABS and is based upon proven passive radio frequency identification technology (RFID). Physical size is a nominal 1.5 x 1.2 x 0.15 inches (36x29x3.8 mm), making it one of the absolute smallest proximity key ring tags available.</p> |
|  | <h3>Specifications HC-HARPS14</h3> <p>Read Range a: HC-P300 - Up to 3 inches (76 mm) P-600 - Up to 3 inches (76 mm) HC-P400 - Up to 1 inch (25 mm) P-700 - Up to 10 inches (254 mm) P-500 - Up to 4 inches (102 mm)</p> <p>Size: Nominal 3.38 x 2.12 x 0.031 inches (85.9 x 53.8 x 0.79 mm)</p> <p>Weight: 0.19 oz. (5.5 g)</p> |



Powered by Thought...
Driven by Technology
www.hartmann-controls.com

Operation: Passive (no battery)
Frequency: 125 KHz excitation
Humidity: 0-95% non-condensing
Operating Temperature: -40° C to +65° C
Material: PVC**Color:** Glossy White
Slot Punch: Vertical and Horizontal Indicators
Marking: Date Code and ID

Graphics Quality Prox Card ISO Compliant Thickness for Badging Graphics Quality, Both Sides, Standard! Portrait or Landscape Punch Capability No Diminished Read Range Available with magnetic stripe (GRMAG)